

Engage consumers. Offer multiple payment options. One device for cash & cashless.

Part of Nayax's cashless payment solution for unattended automated machines

- ▶ Complete management and telemetry suite
- ▶ Reports & real-time data gathering capabilities
- ▶ Easy navigation with color touchscreen
- ▶ Consumer engagement tools
- ▶ Features bill validator support



1

Part of a complete solution

A card reader with cash options, cashless clearance, telemetry & monitoring, and remote management

2

Boosts revenue

- ▶ More payment choices increase sales
- ▶ Credit and debit cards – swipe, contact & contactless
- ▶ Mobile apps, QR codes and prepaid cards

3

Cash capabilities

- ▶ Combo bezel for bill validator
- ▶ Track cash collections
- ▶ Cash accountability

4

Reporting capabilities

- ▶ Real-time data transmission
- ▶ Inventory and cash monitoring, alerts & reports
- ▶ Continuously updated information on all aspects of operation

5

Communicate with your consumers

- ▶ Voice interaction, in local language
- ▶ Multiple language display capacity
- ▶ Customizable color touchscreen


6

Dynamic marketing tools

- ▶ Promote your business
- ▶ Develop customer loyalty with promotions
- ▶ Offer punch cards & loyalty discounts
- ▶ Advertise via color touchscreen



Cashless payment card reader with bill validator support



A complete payment solution for unattended automated machine operators

Benefit from easy installation, clearance, monitoring, cash accountability and management

Interface & Management	
Display Screen	Color Touch LCD Display 2.4 inch IPS 320 x 240 Pixels + 4 LEDs + 6 soft touch buttons
Architecture	ARM Technology - 2 x Cortex, 32 bit, 180/216MHz
Audio	Speaker + Buzzer
Localization	Multi-language support - LCD text & voice audio instructions
Power Supply	Operating voltage: 12-42V DC, 12-24V AC; 5 Watts. Recommended External Power Supply: 24V DC / 2Amp
Security	Support of DES, 3DES, AES, RSA, ECC, SHA1 algorithms, Random Number Generator
External Interface	Ethernet, 2 X RS232 (RS232 or TTL level through SW), USB Device, External reader, 1 X door open sensor, 1 X temperature sensor
Anti-Vandal	Internal shock/tilt detector, anti-vandal Dragontrail glass
Power-Loss Protection	Super Caps with safe shutdown mechanism
Pulse Input/Output	6 in/out interfaces + 1 input (Inhibit)
Communication	3G / 4G / Ethernet / NFC
Machine Protocols	MDB / DEX / DDCMP / Pulse / VCCS / ccTalk / JVMA
Safety	CE, FCC*, RoHS

*Q1 2020

Payment Support			
Contact	100,000 insertion cycles EMV Level 1 EMV Level 2	Contactless	EMV Level 1, FeliCa Level 2: Visa payWave, MasterCard PayPass, UnionPay qPBOC, AMEX ExpressPay, JCB J/Speedy, Discover D-PAS, CUP QuickPass
Magnetic Stripe	ISO 7811 and JIS I Tracks 1,2,3 ; JIS II	Cash	Cash acceptance via a third party bill validator
Other Cards Supported	13.56 MHz : NFC, MIFARE, ISO 14443 Type A and B, ISO 15693, SONY® FeliCa		

Installation Environment	
Operating Temperature	-20°C to 55°C / -4°F to 131°F
Storage Temperature	-40°C to 85°C / -40°F to 185°F
Humidity	25% to 95% (non-condensing)
Flammability	UL-94 V0

Let Nayax help your business maximize your profits.
Contact us today to learn more.

www.nayax.com